

# CIERRE MECÁNICO TIPO: CM58B Y CM59B

Datos Técnicos:

Equilibrado.

Cierre Simple.

Independiente del sentido de giro.

Presión: 62 BAR

Temperatura: -50 a 200°C


Velocidad: 20 m/seg.



CM59B



CM58B



Tipo	Ø	d1	d2	D1	D2	D3	D4	d0	L	L1	L2	L3
		h6		H8	H11							
CM59B-14		14	18	25	21	32	34	3	49.5	42.5	30.5	24.5
CM59B-16		16	20	27	23	34	36	3	49.5	42.5	30.5	24.5
CM59B-18		18	22	33	27	36	38	3	52.5	45	31.5	25
CM59B-20		20	24	35	29	38	40	3	52.5	45	31.5	25
CM59B-22		22	26	37	31	40	42	3	52.5	45	31.5	25
CM59B-24		24	28	39	33	42	44	3	54.5	47.5	34.2	27.5
CM59B-25		25	30	40	34	44	46	3	54.5	47.5	34.5	27.5
CM59B-28		28	33	43	37	47	49	3	57	50	37.2	30
CM59B-30		30	35	45	39	49	51	3	57	50	38	30
CM59B-32		32	38	48	42	54	58	3	57	50	38	30
CM59B-33		33	38	48	42	54	58	3	57	50	38	30
CM59B-35		35	40	50	44	56	60	3	57	50	38	30
CM59B-38		38	43	56	49	59	63	4	59.5	52.5	39.5	29.5
CM59B-40		40	45	58	51	61	65	4	59.5	52.5	39.5	29.5
CM59B-43		43	48	61	54	64	68	4	59.5	52.5	39.5	29.5
CM59B-45		45	50	63	56	66	70	4	59.5	52.5	39.5	29.5
CM59B-48		48	53	66	59	69	73	4	59.5	52.5	39.5	29.5
CM59B-50		50	55	70	62	71	75	4	64.5	57.5	44	32.5
CM59B-53		53	58	73	65	78	83	4	64.5	57.5	44	32.5
CM59B-55		55	60	75	67	80	85	4	64.5	57.5	44	32.5
CM59B-58		58	63	78	70	83	88	4	69.5	62.5	49	37.5
CM59B-60		60	65	80	72	85	90	4	69.5	62.5	49	37.5
CM59B-63		63	68	83	75	88	93	4	69.5	62.5	49	37.5
CM59B-65		65	70	85	77	90	95	4	69.5	62.5	49	37.5
CM59B-70		70	75	92	83	99	104	4	77	70	55.5	42
CM59B-75		75	80	97	88	104	109	4	77	70	55.5	42
CM59B-80		80	85	105	95	109	114	4	77	70	55	42
CM59B-85		85	90	110	100	114	119	4	82	75	60	47
CM59B-90		90	95	115	105	119	124	4	82	75	60	47
CM59B-95		95	100	120	110	124	129	4	82	75	60	47
CM59B-100		100	105	125	115	129	134	4	82	75	60	47