

CIERRE MECÁNICO TIPO: CM58U Y CM59U

Datos Técnicos:

No equilibrado.



Cierre Simple.

Independiente del sentido de giro.

Temperatura: -20°C a 200°C

Presión: 17 BAR

Velocidad: 20 m/seg



TIPO	∅	d0 h6	D1 H11	D2 H8	D0	d1	L1	L2	L3	L4
CM59U-20		20	29	35	36	34	45	24	13.5	9
CM59U-22		22	31	37	38	36	45	24	13.5	9
CM59U-24		24	33	39	40	38	47	26.7	13.3	9
CM59U-25		25	34	40	41	39	47	27	13	9
CM59U-28		28	37	43	44	42	50	30	12.5	9
CM59U-30		30	39	45	46	44	50	30.5	12	9
CM59U-32		32	42	48	48	46	50	30.5	12	9
CM59U-33		33	42	48	49	47	50	30.5	12	9
CM59U-35		35	44	50	51	49	50	30.5	12	9
CM59U-38		38	49	56	58	54	52	32	13	9
CM59U-40		40	51	58	60	56	52	32	13	9
CM59U-43		43	54	61	63	59	52	32	13	9
CM59U-45		45	56	63	65	61	52	32	13	9
CM59U-48		48	59	66	68	64	52	32	13	9
CM59U-50		50	62	70	70	66	55	34	13.5	9
CM59U-53		53	65	73	73	69	55	34	13.5	9
CM59U-55		55	67	75	75	71	55	34	13.5	9
CM59U-58		58	70	78	83	75	60	39	13.5	9
CM59U-60		60	72	80	85	80	60	39	13.5	9
CM59U-63		63	75	83	88	83	60	39	13.5	9
CM59U-65		65	77	85	90	85	60	39	13.5	9
CM59U-68		68	81	90	93	88	60	39	13.5	9
CM59U-70		70	83	92	95	90	67	45.5	14.5	9
CM59U-75		75	88	97	104	95	67	45.5	14.5	9
CM59U-80		80	95	105	109	104	67	45	15	9
CM59U-85		85	100	110	114	109	67	45	15	9
CM59U-90		90	105	115	119	114	72	50	15	9
CM59U-95		95	110	120	124	119	72	50	15	9
CM59U-100		100	115	125	129	124	72	50	15	9